


# 21.5' Wall Mounting Touch Kiosk(Monitor)



● **24/7 Commercial Use**

Industrial-grade Power Supply  
30,000-hour extended life LCD display

● **Android / Windows Optional**

Android 11 default, High-end spec optional  
Latest Celeron J6412 default  
i5 12Gen Optional

● **Free customization**

Multiple peripheral configurations available  
integrate your own POS terminal

● **Easy wall mount or Floor Mount**

Wall mount bracket by default  
Optional with pre-drilled holes for floor mounting

**Monitor configuration**

CPU	68676
HDMI in	*1
VGA	*1
USB for touch	*1

**LCD Panel**

Screen diagonal	21.5inch
Display active screen size (mm)	476.64*268.11 mm
Aspect ratio	16:9
Physical resolution	1920*1080
Colours displayed	16.7M
Brightness (cd/m <sup>2</sup> )	≥250
Contrast	1000:1
Visual Angle H/V (°)	178/178
Backlight Lifetime (hours)	LED 30,000
Refresh Rate	60 Hz

**Touch Panel**

Touch technology	PCAP
Response time	<5ms
Touch points	10 points standard
Touch effective recognition	>1.5mm
Scanning Frequency	200Hz
Scanning accuracy	4096×4096
Working Current/Voltage	180Ma/DC+5V±5%
Surface Hardness	Mohs class 7 explosion-proof glass

**Operation Environment**

Operation Temperature	0°C-50°C
Operation Humidity	10% - 80%
Storage Temperature	-5°C-60°C
Storage Humidity	10% - 85%

**Dimension**

Machine(mm)	527 (W) ×426 (L) × 46.7 (T) mm
Package(mm)	570 (W) ×440 (L) × 145 (T) mm
Net weight	5.35 kg
Gross weight	7.45 kg

**Power supply parameters**

Power Input	110-240V AC 50/60Hz
Power Output	DC 12V 3A
Standby power consumption	≤0.5W
Overall power consumption	<30W

**External Connectors**

HDMI	x1
Power Socket	x1
USB 2.0	x2

**Included in the Delivery**

Manual	x1
Wall mount bracket	x1
AC Power cable	x1

**Use Case**



## Peripherals

The GD 215E Kiosk comes equipped with a high-speed thermal printer, a QR code scanner, and an RFID card reader. Its versatile design allows for compatibility with a wide range of peripherals, and the option to customize with or without specific devices. With a short customization period ranging from 7 to 35 days, delivery can be completed efficiently.



### Thermal Printer

Model MS-E801  
Printing Speed 250MM/S(MAX)  
Printing Width 72MM  
Paper Width 80MM(MAX)  
Resolution 576dots/line  
Paper Roll Dia 80MM(MAX)  
Paper Cut Auto Cut



### Barcode Scanner

Model EMT8020  
Resolution 640\*480 COMS  
Recognition Accuracy 5mil  
Field of View Horizontal 68°, Vertical 51°  
2D Codes PDF417, QR Code, DataMatrix, etc  
1D Codes Code 128, EAN-13, EAN-8, Code 39,



### RFID card reader

Model M11  
Frequency: IC Mifare1/; CPU/TypeA; 14443A  
Protocols: IC/ID  
Supported Ca 80MM(MAX)  
Functions: Read/Write IC cards, Read ID cards

### More Options for customization



Fingerprint Sensor



Metal Keyboard



Card Dispenser



Payment terminal



Camera



NFC-Payment



4G LTE



Battery-UPS